

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

ALCO-SENSOR IV WITH PRINTER MAINTENANCE REPORT

RECEIVED

By Carol Day at 9:53 am, Sep 05, 2014

Send copy to Department of Health at	PRINTER SN			DATE OF INCREASION	
030451		95.111.05	3	DATE OF INSPECTION 09-04-14	
LOCATION OF INSTRUMENT (STREET AND C	•			TIME OF INSPECTION	<u> </u>
CHECKLIST: Place a mark in the hour	1 Faraon St. Joseph MC	64501		1603	···
CHECKLIST: Place a mark in the box ues where determined.) Unmarked ite	. by each item it found to ms must be corrected by	be satisfactory or if	f operating within esta	blished limits. (Write In o	bserved va
DIGITAL READOUT (ALL ELEME		erore daing mandine			<u></u>
\$				· .	
TEMPERATURE OF ALCO SENSO					
PRINTER WORKING PROPERLY	-				
TIME AND DATE DISPLAYING PF					
BREATH ALCOHOL ACCURACY STA	NDARDS				
SIMULATOR SOLUTION		🛛 сомы	RESSED ETHANOL-C	GAS MIXTURE	
STANDARD SUPPLIER	Intoximeters	LOT # AG3	800201 EXP. DAT	E 01-02-2015	•
SIMULATOR TEMPERATURE (34	'C ± 0.2'C)	SIMULATOR SN _	SIMU	JLATOR EXP DATE	
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 10.080% STAND	olution. All three tests m o the standard solution I READ BETWEEN 0.095° READ BETWEEN 0.076°	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE	T)	l of .005 or
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 0.040% STANDARD - MUST FOR THE CONTROL OF THE CONTROL OF THE CALIBRATION O	olution. All three tests m o the standard solution I READ BETWEEN 0.095° READ BETWEEN 0.076°	BE USED PER MAI nust be within ±5% of being used. (PRINT % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE LUSIVE	T) and must have a spread	of .005 or
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 0.040% STANDARD - MUST ROUST TO 0.040% STANDARD - MUST ROUST	olution. All three tests mother standard solution in READ BETWEEN 0.0959 READ BETWEEN 0.07698 READ BETWEEN 0.0389	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE	T)	of .005 or
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 0.080% STANDARD - MUST FOR 0.040% STANDARD - MUST FOR 0.040% STANDARD - MUST FOR 0.102 RFI DETECTOR OPERATING	olution, All three tests mother standard solution in READ BETWEEN 0.095° READ BETWEEN 0.076° READ BETWEEN 0.038° READ BETWEEN	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE LUSIVE TEST 3	r) and must have a spread	1 of .005 or
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 0.080% STANDARD - MUST FOR 0.040% STANDARD - MUST FOR THE STANDARD -	olution. All three tests mother standard solution in READ BETWEEN 0.0959 READ BETWEEN 0.0769 READ BETWEEN 0.0389 TESTS IN THE FOLLO	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE LUSIVE TEST 3	r) and must have a spread	l of .005 or
CALIBRATION CHECK - (ONLY OF Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR 0.080% STANDARD - MUST FOR 0.040% STANDARD - MUST FOR	olution. All three tests mother standard solution in READ BETWEEN 0.0959 READ BETWEEN 0.0769 READ BETWEEN 0.0389 TESTS IN THE FOLLO	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE LUSIVE TEST 3	r) and must have a spread	1 of .005 or
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR THE	olution. All three tests mother standard solution in READ BETWEEN 0.095° READ BETWEEN 0.076° READ BETWEEN 0.038° READ BETWEEN 0.038° READ BETWEEN 0.038° READ BETWEEN 0.038° READ TESTS IN THE FOLLORED TESTS)	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR THE	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOR THE STANDARD FOR T	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOUNDARD - MUST F	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN	nd must have a spread .102 NTENANCE REPORT:	
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOUNDARD - MUST F	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN 9 (.1519) store the instrument to	nd must have a spread .102 NTENANCE REPORT: 1 (OVER .19) to operate satisfactorily a	2 and within
CALIBRATION CHECK - (ONLY ON Run three tests using a standard so less. Check the box corresponding to 0.100% STANDARD - MUST FOUNDARD - MUST F	olution. All three tests mo the standard solution I READ BETWEEN 0.095 READ BETWEEN 0.076 READ BETWEEN 0.0389 TEST 2 - TESTS IN THE FOLLO RED TESTS) (.0509) gration or modification testing the standard solution.	BE USED PER MAI nust be within ±5% of being used. (PRINT) % and 0.105% INCL % and 0.084% INCL % and 0.042% INCL .102 DWING RANGES SI	NTENANCE REPORT of the standard value OUT ATTACHED) LUSIVE LUSIVE TEST 3 - NCE THE LAST MAIN 9 (.1519) store the instrument to	nd must have a spread .102 NTENANCE REPORT: (OVER .19) to operate satisfactorily a	2 and within

AIDAS.

Airgas Mid America (LABORATORY)

3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100

Fax: (314) 533-7328

Certificate of Analysis

Customer Name Intoximeters, Inc. 2081 Craig Road St. Louis, Mo 63146

Test Date: 2-Jan-2013

Dear Sir,

This is your Certificate of Analysis:

Exp. Date 1/2/2015

Cyl, Type 108 Component Ethanol

Nitrogen

Certified Concentration 0.100 ± 2% BrAC (272 ppm)

Balance

Lot#

AG300201

Certification Traceable to N.I.S.T. RGM Ethanol Standards:

<u>Serial No.</u>	<u>Concentration</u>	<u>Serial No.</u>	Concentration
EB0010581	391.5 ppm	EB0010603	390.9 ppm
EB0010570	258.4 ppm	EB0010559	258.3 ppm
EB0010285	208.9 ppm	EB0010595	209.2 ppm
EB0010561	101.9 ppm	EB0010562	104.9 ppm
EB0010561	101.9 ppm	EB0010562	104.9 ppm
EB0010681	53.0 ppm	EB0010579	52.4 ppm

Analytical Method:

NDIR

ISO 17025:2005 A2LA accredited. Certificate Number 2989.01



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



PERMIT TYPE II

WAYNE BRYOM

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

ALCO-SENSOR IV WITH PRINTER, DATAMASTER

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE5/19/2014	honse
	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
NUMBER 240241	Dal Vacheran
EXPIRES 5/19/2016	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES
MO 580-0771 (6-10)	LAB4 (R6-10)



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM

INSTRUMENT OPERATOR CARD

The named cardholder is authorized to operate an evidential breath alcohol instrument for the determination of the alcoholic content in breath form of expired all In Alternation.



Operator

BRYOM, WAYNE

Permit No 240241

Date Issued 5/19/2014 Date Expires 5/19/2016